



**SOUTH ELEVATION**  
 S: 1/4" = 1'-0"

EXTERIOR MATERIALS/FINISHES			
<b>A</b> BRICK, STANDARD SIZE, 2 2/3" x 8" x 4", COLOR REDDISH BROWN AS APPROVED BY OWNER	<b>C</b> LIMESTONE/PRAIRIE STONE, 3 5/8" THICK, CONTINUOUS LENGTH x HEIGHTS SHOWN, COLOR ALABASTER (WHITE), GROUND FACE	<b>E</b> LIMESTONE/PRAIRIE STONE, WINDOW SILLS, PROJECT 3/4" PAST ADJACENT BAND, W/ DRIP BASE, COLOR ALABASTER (WHITE), GROUND FACE	<b>I</b> ROOF SHINGLES #300, 30 YEAR WARRANTY, ONE LAYER OF 15# FELT & "ICE" UNDERLAYMENT PROTECTION UP TO 30" FROM EDGE OF ROOF
<b>B</b> 2'-0" x 8'-0" BRICK QUIONS @ ALL CORNERS, PROJECT BEYOND ADJACENT BRICK BY 3/4"	<b>D</b> LIMESTONE/PRAIRIE STONE, WINDOW HEADER & SIDE TRIM WHERE INDICATED, COLOR ALABASTER (WHITE), GROUND FACE	<b>F</b> TRIM 5/4 BOARD (1" THICK x 12"H) @ ROOF HORIZONTAL FASCIAS @ TOP OF WALL, SELECT CEDAR MILL TEXTURE, COLOR ARTIC WHITE, JHIO-20	<b>J</b> ALUMINUM ROOF IN "PATINA GREEN" COLOR OVER NORTH ENTRY, PROJECTING NORTH WINDOW @ ROOF LEVEL, & ROOF OVER WEST ENTRY
<b>NOTES:</b> 1. ALL MASONRY DIMENSIONS ARE NOMINAL SIZES UNLESS OTHERWISE NOTED (UNO) 2. INSTALLERS OF JAMES HARDIE FIBER-CEMENT BUILDING PRODUCTS SHALL OBTAIN AND FOLLOW THE BEST PRACTICES-INSTALLATION GUIDE, SIDING AND TRIM PRODUCTS VERSION 3.1 (OR LATEST VERSION) FOR INSTALLATION OF HARDIE PLANK, HARDIE SHINGLE, HARDIE PANEL, HARDIE TRIM, HARDIE SOFFIT AND OTHER HARDIE PRODUCTS THAT MAY BE INSTALLED ON THE EXTERIOR OF THIS BUILDING COMPLEX.	<b>G</b> ALUMINUM GUTTERS & DOWNSPOUTS W/ PRECAST CONCRETE SPLASHBLOCKS @ GRADE	<b>H</b> 1'-4" ROUND FIBERGLASS COLUMNS BY SUPERIOR, 12" @ BASE, CUT 3/8" OFF BASE OF COLUMN TO FIT, PRIMED AND PAINTED BY CONTRACTOR, WHITE	<b>K</b> FLANK LAP SIDING, 8 1/4" (7" EXPOSURE) x 12'-0" LONG, SELECT CEDARMILL TEXTURE/STYLE, COLOR TO BE ARTIC WHITE, JHIO-20
			<b>L</b> TRIM 5/4 BOARD (1" THICK x 10"H) @ FASCIA OVER ROOF DORMERS, SELECT CEDARMILL TEXTURE, COLOR TO BE ARTIC WHITE, JHIO-20